

# FIRMWARE V4.00 RELEASE NOTES

## **EZ-Guide® Plus Lightbar Guidance System**

- **Introduction**
- **Major new features and enhancements**
- **Minor Enhancements**
- **T2 Terrain Compensation Technology Operation**
- **Upgrade procedure**

Version 4.00  
Part Number 61029-XX-ENG  
Revision A  
September 2006

**Contact Information**

Trimble Navigation Limited  
Agriculture Division  
10355 Westmoor Dr  
Suite #100  
Westminster, CO 80021  
USA

+1-913-495-2700 Phone  
[www.EZ-Guide.com](http://www.EZ-Guide.com)

**Copyright and Trademarks**

© 1999–2006, Trimble Navigation Limited. All rights reserved. Trimble, AgGPS, EZ-Guide, and EZ-Steer are trademarks of Trimble Navigation Limited, registered in the United States Patent and Trademark Office and in other countries. Autopilot, Autoseed, EZ-Boom, EZ-Toolbox, FieldManager, Freeplay, OnPath, and T2 are trademarks of Trimble Navigation Limited.

All other trademarks are the property of their respective owners.

**Release Notice**

This is the September 2006 release (Revision A) of the *EZ-Guide Plus Lightbar Guidance System Release Notes*, part number 61029-XX-ENG. It applies to version 4.00 of the EZ-Guide Plus lightbar guidance system firmware.

**Limited Warranty Terms and Conditions****Product Limited Warranty**

Subject to the terms and conditions set forth herein, Trimble Navigation Limited ("Trimble") warrants that for a period of (1) year from date of purchase this Trimble product (the "Product") will substantially conform to Trimble's publicly available specifications for the Product and that the hardware and any storage media components of the Product will be substantially free from defects in materials and workmanship.

**Product Software**

Product software, whether built into hardware circuitry as firmware, provided as a standalone computer software product, embedded in flash memory, or stored on magnetic or other media, is licensed and not sold. If accompanied by a separate end user license agreement, use of any such software will be subject to the terms of such end user license agreement (including any differing limited warranty terms, exclusions and limitations), which shall control over the terms and conditions set forth in this limited warranty).

**Software Updates**

During the limited warranty period you will be entitled to receive such Fix Updates and Minor Updates to the Product software that Trimble releases and makes commercially available and for which it does not charge separately, subject to the procedures for delivery to purchasers of Trimble products generally. If you have purchased the Product from an authorized Trimble distributor rather than from Trimble directly, Trimble may, at its option, forward the software Fix Update or Minor Update to the Trimble distributor for final distribution to you. Major Upgrades, new products, or substantially new software releases, as identified by Trimble are expressly excluded from this update process and limited warranty. Receipt of software updates shall not serve to extend the limited warranty period.

For purposes of this warranty the following definitions shall apply: (1) "Fix Update" means an error correction or other update created to fix a previous software version that does not substantially conform to its published specifications; (2)

"Minor Update" occurs when enhancements are made to current features in a software program; and (3) "Major Upgrade" occurs when significant new features are added to software, or when a new product containing new features replaces the further development of a current product line. Trimble reserves the right to determine, in its sole discretion, what constitutes a significant new feature and Major Upgrade.

**Warranty Remedies**

If the Trimble Product fails during the warranty period for reasons covered by this Limited Warranty and you notify Trimble of such failure during the warranty period, Trimble at its option will repair OR replace the nonconforming Product, OR refund the purchase price paid by you for the Product, upon your return of the Product to Trimble in accordance with Trimble's standard return material authorization procedures.

**How to Obtain Warranty Service**

To obtain warranty service for the Product, please contact your Trimble dealer. Alternatively, you may contact Trimble to request warranty service at +1-408-481-6940 (24 hours a day) or e-mail your request to [trimble\\_support@trimble.com](mailto:trimble_support@trimble.com). Please be prepared to provide:

- your name, address, and telephone numbers
- proof of purchase
- this Trimble warranty card
- a description of the nonconforming Product including the model number
- an explanation of the problem.

The customer service representative may need additional information from you depending on the nature of the problem.

**Warranty Exclusions and Disclaimer**

This Product limited warranty shall only apply in the event and to the extent that (i) the Product is properly and correctly installed, configured, interfaced, maintained, stored, and operated in accordance with Trimble's applicable operator's manual and specifications, and; (ii) the Product is not modified or misused. This Product limited warranty shall not apply to, and Trimble shall not be responsible for defects or performance problems resulting from (i) the combination or utilization of the Product with hardware or software products, information, data, systems, interfaces or devices not made, supplied or specified by Trimble; (ii) the operation of the Product under any specification other than, or in addition to, Trimble's standard specifications for its products; (iii) the unauthorized, installation, modification, or use of the Product; (iv) damage caused by: accident, lightning or other electrical discharge, fresh or salt water immersion or spray; or exposure to environmental conditions for which the Product is not intended; or (v) normal wear and tear on consumable parts (e.g., batteries). Trimble does not warrant or guarantee the results obtained through the use of the Product. NOTICE REGARDING PRODUCTS EQUIPPED WITH GPS TECHNOLOGY: TRIMBLE IS NOT RESPONSIBLE FOR THE OPERATION OR FAILURE OF OPERATION OF GPS SATELLITES OR THE AVAILABILITY OF GPS SATELLITE SIGNALS.

THE FOREGOING LIMITED WARRANTY TERMS STATE TRIMBLE'S ENTIRE LIABILITY, AND YOUR EXCLUSIVE REMEDIES, RELATING TO PERFORMANCE OF THE TRIMBLE PRODUCT. EXCEPT AS OTHERWISE EXPRESSLY PROVIDED HEREIN, THE PRODUCT AND ACCOMPANYING DOCUMENTATION AND MATERIALS

ARE PROVIDED "AS-IS" AND WITHOUT EXPRESS OR IMPLIED WARRANTY OF ANY KIND, BY EITHER TRIMBLE OR ANYONE WHO HAS BEEN INVOLVED IN ITS CREATION, PRODUCTION, INSTALLATION, OR DISTRIBUTION, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE, TITLE, AND NONINFRINGEMENT. THE STATED EXPRESS WARRANTIES ARE IN LIEU OF ALL OBLIGATIONS OR LIABILITIES ON THE PART OF TRIMBLE ARISING OUT OF, OR IN CONNECTION WITH, ANY PRODUCT.

SOME STATES AND JURISDICTIONS DO NOT ALLOW LIMITATIONS ON DURATION OR THE EXCLUSION OF AN IMPLIED WARRANTY, SO THE ABOVE LIMITATION MAY NOT APPLY TO YOU.

#### Limitation of Liability

TRIMBLE'S ENTIRE LIABILITY UNDER ANY PROVISION HEREIN SHALL BE LIMITED TO THE AMOUNT PAID BY YOU FOR THE PRODUCT. TO THE MAXIMUM EXTENT PERMITTED BY APPLICABLE LAW, IN NO EVENT SHALL TRIMBLE OR ITS SUPPLIERS BE LIABLE FOR ANY INDIRECT, SPECIAL, INCIDENTAL OR CONSEQUENTIAL DAMAGE WHATSOEVER UNDER ANY CIRCUMSTANCE OR LEGAL THEORY RELATING IN ANYWAY TO THE PRODUCTS, SOFTWARE AND ACCOMPANYING DOCUMENTATION AND MATERIALS, (INCLUDING, WITHOUT LIMITATION, DAMAGES FOR LOSS OF BUSINESS PROFITS, BUSINESS INTERRUPTION, LOSS OF DATA, OR ANY OTHER PECUNIARY LOSS), REGARDLESS OF WHETHER TRIMBLE HAS BEEN ADVISED OF THE POSSIBILITY OF ANY SUCH LOSS AND REGARDLESS OF THE COURSE OF DEALING WHICH DEVELOPS OR HAS DEVELOPED BETWEEN YOU AND TRIMBLE. BECAUSE SOME STATES AND JURISDICTIONS DO NOT ALLOW THE EXCLUSION OR LIMITATION OF LIABILITY FOR CONSEQUENTIAL OR INCIDENTAL DAMAGES, THE ABOVE LIMITATION MAY NOT APPLY TO YOU.

**PLEASE NOTE: THE ABOVE TRIMBLE LIMITED WARRANTY PROVISIONS WILL NOT APPLY TO PRODUCTS PURCHASED IN THOSE JURISDICTIONS, SUCH AS COUNTRIES OF THE EUROPEAN ECONOMIC COMMUNITY, IN WHICH PRODUCT WARRANTIES ARE OBTAINED FROM THE LOCAL DISTRIBUTOR. IN SUCH CASE, PLEASE CONTACT YOUR TRIMBLE DEALER FOR APPLICABLE WARRANTY INFORMATION.**

#### Registration

To receive information regarding updates and new products, please contact your local dealer or visit the Trimble website at [www.trimble.com/register](http://www.trimble.com/register). Upon registration you may select the newsletter, upgrade or new product information you desire.

#### Notices

##### Notice to Our European Union Customers

For product recycling instructions and more information, please go to [www.trimble.com/ev.shtml](http://www.trimble.com/ev.shtml)

Recycling in Europe: To recycle Trimble WEEE (Waste Electrical and Electronic Equipment, products that run on electrical power.), call +31 497 53 24 30, and ask for the "WEEE Associate".



Or, mail a request for recycling instructions to:

Trimble Europe BV  
c/o Menlo Worldwide Logistics  
Meerheide 45  
5521 DZ Eersel, NL

#### End User License Agreement

**IMPORTANT, READ CAREFULLY.** THIS END USER LICENSE AGREEMENT ("AGREEMENT") IS A LEGAL AGREEMENT BETWEEN YOU AND TRIMBLE NAVIGATION LIMITED and applies to the computer software provided with the Trimble product purchased by you (whether built into hardware circuitry as firmware, embedded in flash memory or a PCMCIA card, or stored on magnetic or other media), or provided as a stand-alone computer software product, and includes any accompanying printed materials and any "online" or electronic documentation ("Software"). The Software also includes any software (including, without limitation, upgrades and updates), that you download from Trimble's Web site. BY CLICKING "YES" IN THE ACCEPTANCE BOX, OR BY INSTALLING, COPYING OR OTHERWISE USING THE SOFTWARE, YOU AGREE TO BE BOUND BY THE TERMS OF THIS AGREEMENT. IF YOU DO NOT AGREE TO THE TERMS OF THIS AGREEMENT, PROMPTLY RETURN THE UNUSED SOFTWARE AND ACCOMPANYING TRIMBLE PRODUCT TO THE PLACE FROM WHICH YOU OBTAINED THEM FOR A FULL REFUND.

This Software is protected by copyright laws and international copyright treaties, as well as other intellectual property laws and treaties. The Software is licensed, not sold.

#### 1. SOFTWARE PRODUCT LICENSE

1.1 **License Grant.** This Agreement grants you a non-exclusive right to use one copy of the Software in a machine-readable form on any computer system. Such use is limited to use with Trimble products on any computer hardware and operating system for which it was intended. You may move the Software from one computer to another but may only use the Software on one computer at any time. If you are a business rather than an individual, you may authorize the personnel associated with your business to use the Software, but only one person at one time, on one computer at one time. You may also store or install a copy of the Software on a storage device, such as a network server, used only to install or run the Software on your other computers over an internal network; but in such case you must acquire and dedicate a license for each separate computer on which the Software is installed or run from the storage device. A license for the Software may not be shared or used concurrently on different computers.

1.2 **Other Rights and Limitations.** (1) The Software contains valuable trade secrets proprietary to Trimble and its suppliers. To the extent permitted by relevant law, you shall not, nor allow any third party to copy, decompile, disassemble or otherwise reverse engineer the Software, or attempt to do so, provided, however, that to the extent any applicable mandatory laws (such as, for example, national laws implementing EC Directive 91/250 on the Legal Protection of Computer Programs) give you the right to perform any of the aforementioned activities without Trimble's consent in order to gain certain information about the Software for purposes specified in the respective statutes (i.e., interoperability), you hereby agree that, before exercising any such rights, you shall first request such information from Trimble in writing detailing the purpose for which you need the information. Only if and after Trimble, at its sole discretion, partly or completely denies your request, may you exercise such statutory rights. (2) This Software is licensed as a single product. You may not separate its component parts for use on more than one computer. (3) You may not rent, lease, or lend,

the Software unless you are a reseller of Trimble products under separate written agreement with Trimble and authorized by Trimble to do so. (4) No service bureau work, multiple-user license or time-sharing arrangement is permitted. For purposes of this Agreement "service bureau work" shall be deemed to include, without limitation, use of the Software to process or to generate output data for the benefit of, or for purposes of rendering services to any third party over the Internet or other communications network. (5) You may permanently transfer all of your rights under this Agreement, provided you retain no copies, you transfer all of the Software (including all component parts, the media and printed materials, any upgrades, and this Agreement) and the recipient agrees to the terms of this Agreement. If the Software portion is an upgrade, any transfer must include all prior versions of the Software. (6) You may not export the Software or underlying technology in contravention of applicable U.S. and foreign export laws. (7) Without prejudice as to any other rights, Trimble may terminate this Agreement without notice if you fail to comply with the terms and conditions of this Agreement. In such event, you must destroy all copies of the Software and all of its component parts.

**1.3 Copyright.** All title and copyrights in and to the Software (including but not limited to any images, photographs, animations, video, audio, music, and text incorporated into the Software), the accompanying printed materials, and any copies of the Software are owned by Trimble and its suppliers. You shall not remove, cover or alter any of Trimble's patent, copyright or trademark notices placed upon, embedded in or displayed by the Software or on its packaging and related materials. You may, however, either (1) make one copy of the Software solely for backup or archival purposes, or (2) install the Software on a single computer provided you keep the original solely for backup or archival purposes. You may not copy the accompanying printed materials.

**1.4 U.S. Government Restricted Rights.** Use, duplication, or disclosure by the United States Government is subject to restrictions as set forth in this Agreement, and as provided in DFARS 227.7202-1(a) and 227.7202-3(a) (1995), DFARS 252.227-7013(c)(1)(ii) (OCT 1988), FAR 12.212(a) (1995), FAR 52.227-19, or FAR 52.227-14(ALT III), as applicable.

## **2 LIMITED WARRANTY.**

**2.1 Limited Warranty.** Trimble warrants that the Software will perform substantially in accordance with the accompanying written materials for a period of ninety (90) days from the date of receipt. This limited warranty gives you specific legal rights, you may have others, which vary from state/jurisdiction to state/jurisdiction. The above limited warranty does not apply to error corrections, updates or upgrades of the Software after expiration of the ninety (90) day limited warranty period, which are provided "AS IS" and without warranty unless otherwise specified in writing by Trimble. Because the Software is inherently complex and may not be completely free of nonconformities, defects or errors, you are advised to verify your work. Trimble does not warrant that the Software will operate error free or uninterrupted, will meet your needs or expectations, or that all nonconformities can or will be corrected.

**2.2 Customer Remedies.** Trimble's and its suppliers' entire liability, and your sole remedy, with respect to the Software shall be either, at Trimble's option, (a) repair or replacement of the Software, or (b) return of the license fee paid for any Software that does not meet Trimble's limited warranty. This limited warranty is void if failure of the Software has resulted

from accident, abuse, or misapplication. Any replacement Software will be warranted for the remainder of the original warranty period or thirty (30) days, whichever is longer.

**2.3 NO OTHER WARRANTIES.** To the maximum extent permitted by applicable law, Trimble and its suppliers disclaim all other warranties and conditions, either express or implied, including but not limited to, implied warranties and conditions of merchantability and fitness for a particular purpose, title, and noninfringement with regard to the software and the provision of or failure to provide support services. To the extent allowed by applicable law, implied warranties and conditions on the software are limited to ninety (90) days. You may have other legal rights which vary from state/jurisdiction to state/jurisdiction.

**2.4 LIMITATION OF LIABILITY.** Trimble's entire liability under any provision of this Agreement shall be limited to the amount paid by you for the Software license. To the maximum extent permitted by applicable law, in no event shall Trimble or its suppliers be liable for any special, incidental, indirect or consequential damages whatsoever (including, without limitation, damages for loss of business profits, business interruption, loss of business information, or any other pecuniary loss) arising out of the use or inability to use the Software, or the provision of or failure to provide support services, even if Trimble has been advised of the possibility of such damages. Because some states and jurisdictions do not allow the exclusion or limitation of liability for consequential or incidental damages, the above limitation may not apply to you.

**2.5 PLEASE NOTE:** If you have acquired this product from a dealer located in the European Union, the warranty provisions of this Section 2 will not apply. Please contact your dealer for applicable warranty information.

## **3 GENERAL.**

**3.1** This Agreement shall be governed by the laws of the State of California and applicable United States Federal law without reference to "conflict of laws" principles or provisions. The United Nations Convention on Contracts for the International Sale of Goods will not apply to this Agreement. Jurisdiction and venue of any dispute or court action arising from or related to this Agreement or the Software shall lie exclusively in or be transferred to the courts the County of Santa Clara, California, and/or the United States District Court for the Northern District of California. You hereby consent and agree not to contest, such jurisdiction, venue and governing law.

**3.2** Section 3.1 notwithstanding, if you acquired this product in Canada, this Agreement is governed by the laws of the Province of Ontario, Canada. In such case each of the parties to this Agreement irrevocably attorns to the jurisdiction of the courts of the Province of Ontario and further agrees to commence any litigation that may arise under this Agreement in the courts located in the Judicial District of York, Province of Ontario. If you acquired this product in the European Union, this Agreement is governed by the laws of The Netherlands, excluding its rules governing conflicts of laws and excluding the United Nations Convention on the International Sale of Goods. In such case each of the parties to this Agreement irrevocably attorns to the jurisdiction of the courts of The Netherlands and further agrees to commence any litigation that may arise under this Agreement in the courts of The Hague, The Netherlands.

**3.3** Trimble reserves all rights not expressly granted by this Agreement.

---

## Introduction

These release notes describe new features and changes in the documentation for the EZ-Guide® Plus lightbar guidance system firmware version 4.00. The release notes include features added in version 3.11 and 3.10.

## Contents

These release notes contain information regarding the following:

- Major new features and enhancements
- Minor enhancements
- T2 terrain compensation technology
- Upgrade procedure

---

## Major new features and enhancements

This section lists all the changes since the EZ-Guide Plus system firmware version 3.00. It includes features added in:

- firmware version 4.00
- firmware version 3.11
- firmware version 3.10

### Enhancements to saved vehicle configurations

The EZ-Guide Plus firmware version 4.00 records more vehicle configuration information than previous versions of the firmware.

If you saved an EZ-Steer system vehicle configuration in a previous version of the firmware, that configuration will be incompatible with the firmware version 4.00.

If you have one or more saved vehicle configurations and you want to upgrade to the EZ-Guide Plus firmware version 4.00:

1. Write down your vehicle configuration information.

For more information on which settings to record, see Vehicle configuration parameters on page 8.

2. Upgrade the firmware.
3. Re-enter the vehicle information manually.
4. Save the vehicle configuration.

---

In the EZ-Guide Plus firmware version 4.00, the system must automatically restart to properly load all settings when you reload a saved vehicle configuration.



*Note – The EZ-Guide Plus firmware version 3.11 and 3.10 is also incompatible with earlier saved vehicle configurations.*

## Vehicle configuration parameters

The parameters in the following tables are stored in the vehicle configuration.

*Note – Saved vehicle configurations from previous versions of the firmware are incompatible with the version 4.00 firmware.*

General	Terrain compensation	EZ-Steer	EZ-Boom
Ant/impl offset	Orientation	Antenna/axle offset	Swath width
Swath width	T2 filter	Vehicle type	Boom width
Implement offset	Antenna height	Steering wheel diameter	Number of sections
Pass code	Roll calibration	Angle per turn	Section # width [10]
Autopilot RTK network ID	Hide EZ-Steer menu	Freeplay left	Boom switching
	T2 tech on/off	Freeplay right	Boom control
		Wheel base	Lead in
		EZ-Steer heading filter	Off delay
		Motor speed	Rate control
		Aggressiveness	Rate 1
		Min and max speed	Rate 2
		Engage angle and distance	Allowable error
		Disengage distance	Min flow
		Override sensitivity	Inc/dec step
		Engage on AB	Control valve type
		Operator timeout	Frequency
		Seat switch	Gain
			0 Flow offset
			Response 1
			Response 2
			Threshold
			Dead band
			Sensor enabled
			Set point
			Slope


<b>General</b>	<b>Terrain compensation</b>	<b>EZ-Steer</b>	<b>EZ-Boom</b>
			Flow meter cal
			Target rate
			Speed
			Total nozzles
			Current flow
			Vol/nozzle
			Time elapsed
			Meas'd flow
			Calc'd flow
			Diff flow
			Tank capacity
			Current volume
			Low limit

<b>Lightbar</b>	<b>Guidance</b>	<b>Warnings</b>	<b>GPS</b>
Progress lines on/off	Chase/pull	Headland warning	Min satellites for startup
Adjacent swath on/off	LED spacing	Headland lead time	Max HDOP for startup
Field boundary on/off	Lookahead time	Offline warning	Correction type
AB Line display	Auto-detect turn	Low Acc warning	Correct limit (max correction time)
View mode	Nudge increment	Audible warning	GPS min SNR
Path display			GPS min elevation
Contrast			OnPath™ filter settings
Backlight			PV filter
Brightness			OnPath decay time
LED brightness			VBS backup
Antenna/implement offset			WAAS/EGNOS satellite settings
Lightbar mounting			Autoseed™
Map view and status screen selections			
All Data Port Settings screen options			
Radar pulse output rate			
Radar pulse output angle			
Units			
Language			

*Note – When you reload a saved vehicle configuration, the lightbar must automatically restart to properly load all settings.*

## Improved Select Stored AB screen


When you load a saved AB Line with the *Select Stored AB* option, you can view lines within a specific distance.



By viewing only the lines that are within a certain range, you can narrow the results that you receive. The default range is 3218.7 m (10560 ft).

## Summary view

The summary view shows covered area so you can see any skips or overlaps in material application.




To select the summary view, select  and then press . The summary view appears after the offline view.

## Zooming in the summary view

In the summary view, there are additional zoom features. To access the additional features:

1. Select the summary view.
2. Select .
3. Press . A different set of action icons appears.



Action icon	Description
	End zoom mode
	Move view left
	Move view right
	Move view up
	Move view down
	Center view on the vehicle
	Zoom view in
	Zoom view out

## Path Display

The *Path Display* field has additional options.

The following table shows the effect of the *Path Display* settings on the *Summary* screen:

Item	Description
Off	Coverage is not displayed
On	Coverage is displayed wherever the vehicle drove
Switch	Coverage is displayed whenever it was enabled by an external switch
Engaged	Coverage is displayed wherever the EZ-Steer system was engaged
EZ-Boom	Coverage is displayed wherever the EZ-Boom 2010 system sprayed

To change the *Path Display* setting, select *Lightbar / Display Config*.

## EZ-Boom 2010 system functionality

The EZ-Guide Plus lightbar guidance system firmware version 4.00 contains support for the EZ-Boom™ 2010 automated application control system.

The EZ-Boom 2010 system is a spray controller, offering rate control and automated boom switching for both self-propelled and towed sprayers.


For more information, contact your local reseller, or visit [www.EZ-Boom.com](http://www.EZ-Boom.com).

## Status text

Four status text items appear on the EZ-Guide Plus system main screen. The system displays two items, and then after three seconds displays the other two items.


To change the status text items:

1. On the EZ-Guide Plus lightbar, select *Lightbar / Status Text*. The status text screen appears.




2. To change the status text items that appear on the Map and 3D views, press **OK**.  
Otherwise, press **▼** until you have selected the view that you want to edit and then press **OK**.
3. Press **▲** or **▼** until you have selected the new status text and then press **OK**.
4. Repeat Step 2 for each status text item.

**Note** – To stop the status text items from changing every three seconds, set the first and third items the same, and the second and fourth items the same.



## Remote-engage foot pedal


If you use a foot pedal to engage the EZ-Steer system, the foot pedal must be connected to the optional accessory cable.




For information on purchasing a foot pedal kit (P/N 60941-00), contact your local EZ-Steer system reseller.

To connect the foot pedal to the accessory cable:


1. Cut the pins off the black and white wires on the foot pedal cable and strip about 2.5 cm (1 inch) of insulation off the switch wires.  
*Note – The green wire is not used and can be cut off if required.*
2. Thread each of the black and white switch wires through a cable seal (supplied with the accessory cable).
3. Insert each of the switch wires and the end of the cable seal into a female terminal connector.



4. Crimp the female terminal connectors with an appropriately sized crimp tool or pliers, and then solder to ensure a good physical and electrical connection. Do not allow excess solder to run into other parts of the contact.
5. Insert the two female terminal connectors and the rubber seal into the two holes of the 2-way female connector as follows:
  - Black wire into terminal B.
  - White wire into terminal A.



6. Plug the 2-way female connector into the 2-way male connector on the accessory cable.




7. Run the cable to a clear location on the floor board. Use double-sided tape or wide velcro strips to secure the pedal. Route the cable under the floor mat.



**Tip** – To engage the EZ-Steer system with the remote-engage foot pedal, depress the pedal for 0.5 –3 seconds and then release it when you pass the start of the swath. To avoid accidental engaging, the system engages when you release the pedal. To disengage the EZ-Steer system, turn the steering wheel at the end of the swath, stop, or depress the pedal again.

To enable the remote engage foot pedal:

1. Select *EZ-Steer / External Switch*.



2. Press  $\blacktriangledown$  until *Remote Engage* is displayed.
3. Press  $\text{Ⓢ}$  to save the setting.



**Tip** – You can disable the remote engage foot pedal without disconnecting by selecting the Disable option.

## Default WAAS satellites

There are changes to the WAAS satellites:

- The AOR-W satellite (PRN 122) has moved west.
- There is a new PanAmSat Galaxy 15 satellite (PRN 135) which covers the East Coast of the United States. This means that there is double coverage on the East Coast, where there was previously only a single WAAS satellite providing coverage.
- There is a new Telesat Anik F1R satellite (PRN 138). It is expected to come online in Spring 2007 and will provide double coverage for the central United States.


**Note** – *As of September 2006, the new WAAS satellites are still undergoing testing which may result in reduced accuracy and/or position jumps. The satellites are expected to be fully operational by March 2007.*

The default WAAS satellite settings have changed:


Satellite	Default	Description
PRN-122	Heed Hlth	The system searches for the satellite if the satellite is within the appropriate region and is healthy.
POR	Heed Hlth	
PRN-135	Heed Hlth	
PRN-138	Heed Hlth	

To configure the WAAS satellites:


1. Select *GPS / Corrections*. The *EZ-Guide Plus* screen appears.



2. Select *Edit* and then press  $\odot$ . The *Edit* screen appears.



3. Select *Edit WAAS* and then press  $\odot$ . The *WAAS* screen appears.



4. Select the appropriate WAAS setting for each satellite.

## EGNOS default settings

The default satellite settings for the EGNOS correction service have changed:

Satellite	Default setting	Description
AOR-E	Heed Health	In Heed Health mode, the system searches for the satellite if the receiver is within the appropriate region. If the satellite is not healthy, it is not used.
ARTEMIS	Off	In Off mode, the ARTEMIS satellite is not used.
IOR-W	Heed Health	In Heed Health mode, the system searches for the satellite if the receiver is within the appropriate region. If the satellite is not healthy, it is not used.
IOR	Off	In Off mode, the IOR satellite is not used.

## EZ-Steer system warning message for CNH customers

A new EZ-Steer system warning message is displayed for CNH customers in Europe.

## Large Headlands improved

Guidance update rate and accuracy are improved when driving large headlands.

## Curve recording improved

Curve guidance accuracy has been improved to be 2–3 times better than it was in the version 3.10 firmware.

However, if you do a lot of curve, spiral, or headland patterns, Trimble strongly recommends that you purchase the *AgGPS*® FieldManager™ display and *AgGPS* Autopilot™ system which provide more accurate steering on curves than the EZ-Guide Plus system.


## Row Finder field pattern

There is a Row Finder field pattern which is based on the Adaptive Curve pattern.

This pattern makes it easy to find the correct row to drive down after doing a turn.



**Tip** – Row Finder guidance works on straight or curved rows.



To use the Row Finder field pattern:

1. Set the swath width and implement offset.
2. Set the A point.
3. Drive the first swath.
4. When you reach the end of the row, manually set the B point at the end of the row.
5. Use the offline LEDs and screen to turn onto the next swath.

## Implement offset

If the vehicle has an implement that is offset to one side of the vehicle, configure an implement offset.

To change the implement offset value:

1. Select a new guidance pattern. The *Swath/Implement* screen appears.
2. Select the *Impl. Offset* field.
3. Press ▲ or ▼ until the correct value is displayed.
4. Press Ⓚ.



**Tip** – In some Adaptive Curves, tight U-turns with an implement offset may not be detected if the implement does not follow the path of a U-turn. If this occurs, set *Guidance / Auto-detect Turn* to Off, manually set B, and then turn onto the next curve.

## Area mapping feature


The EZ-Guide Plus lightbar can map area features, calculate the number of acres/hectares, and display the area onscreen while providing guidance.

This feature can be used to mark out an obstacle or excluded area in the field. When the system has finished recording, the number of acres/hectares is calculated and displayed on screen.


To map an area:

1. From the reset guidance screen select New Area.

2. Select the point on the vehicle from which the measurement will be taken (right end of implement, left end of implement, or antenna).



3. Select  to begin mapping the area. The Mapped Area value is continuously updated and displayed on the map screen as you drive around the boundary of the area.



4. Select  or drive back into the start/finish circle to end area mapping.

The mapped area will remain on the screen until the next time power is switched off. Mapped areas are not saved if the power is switched off.

The previously selected AB Line/curve/headland is automatically reloaded after you finish mapping the area.

Only one area can be shown at a time.


The EZ-Guide Plus system does not allow guidance around the mapped area.

If necessary, you can use the pause function to pause mapping to drive around obstacles. When you select the pause/resume icon, a straight line is drawn between the pause and resume points.


## Deleting AB Lines

To delete the current AB Line:

1. Select  to enter the *Guidance Pattern* screen.



2. Select Delete Current AB. The *Confirmation* screen appears.



3. Select Continue to delete the AB Line, or Exit to return to the *Guidance Pattern* screen.

To delete all the stored AB Lines:

1. Select  to enter the *Guidance Pattern* screen.
2. Select Delete All AB's. The *Warning* screen appears.




3. Select Yes to delete all the stored field features, or No to exit.

## Nudge increment

To change the nudge increment, select *Guidance / Nudge Increment*. The default settings are 0' 1" for the EZ-Guide Plus lightbar guidance system and the EZ-Steer assisted steering system, and 0' 0" for the AgGPS Autopilot automated steering system.

## Offline error view

There is a new offline error view which shows the offline distance of the vehicle relative to the guidance line for the last 10 seconds. This screen has a fixed scale of  $\pm 2$  ft. It is very useful for optimizing accuracy when calibrating the EZ-Steer system.




To select this view, press  $\square$ .

**Note** – The offline error view is only available after a field has been defined.

### Pass code

The pass code option can be used to prevent inexperienced operators from modifying the EZ-Guide Plus system configuration settings.

To enable or disable the pass code, select the *Pass Code* screen. The correct pass code is “2005”. You cannot change this pass code.




### Enhancements to Headland spirals

Headland patterns where you spiral to the center of the field without setting an A or B point have been improved. The standard EZ-Guide Plus icons are now available, which allows you to pause, zoom, or change views while defining the headland.

When you drive the headland and then return to the circle for the first time the field is saved immediately.

## Stored AB Lines are numbered

To allow easier identification of the fields in the *Select Stored AB* screen, each field is automatically numbered, and the number appears at the bottom of the screen.



The first three numbers are reserved for headlands and curves. The first straight AB Line or pivot will be number 4.

*Note* – To display the AB number on the main map screen, select *Lightbar / Status Text* and then set one of the status text fields to *Field Num*.

## NMEA input and output

The EZ-Guide Plus system version 3.0 and later allows simultaneous NMEA input and output. This allows position output to a yield monitor, planter, or laptop PC while using an external GPS receiver such as the AgGPS 252/322 receiver.


To simultaneously receive and output NMEA messages, attach the lightbar and external receiver to a computer or device and then configure the lightbar and external receiver.

For more information, refer to the *EZ-Guide Plus Lightbar: Using Simultaneous NMEA Input and NMEA Output Support Note on [www.EZ-Guide.com](http://www.EZ-Guide.com)*.

## Minor Enhancements

### Adaptive curve snapping issue in terraces

Sometimes the lightbar does not select the correct swath on terraces. For example, this can occur when there is not enough room to make a simple U-turn, as shown in the diagram below.



To avoid this issue:

1. Select the *Guidance* screen and then set the Auto-detect Turn option to off.
2. At the end of each swath, manually set a B point.

### New status text options for OmniSTAR XP/HP

When you use OmniSTAR XP/HP with an optional AgGPS 252 or 332 receiver, two new status text options are available:

- *GPS Status* displays the XP/HP status (Convrg./Unconvrg.).
- *Conv Dist.* displays the XP/HP convergence distance.

## Guidance in pivot headlands

When a partial pivot is being driven, the EZ-Guide Plus firmware version 3.11 displays guidance information for the full pivot.

The section of the pivot that is outside the A and B points is defined as headlands and guidance appears as a dotted line.

*Note – When driving beyond the A and B points of a pivot, the Headlands warning still appears.*

## Documentation update


When you drive with an implement offset the arrow shows the center of the implement, rather than the GPS antenna location. This differs from the information in the *EZ-Guide Plus Lightbar Guidance System Getting Started Guide* version 3.00A.

## Other enhancements

The following other enhancements have been made in versions 3.10, 3.11, and 4.00:

- A *GGA Precision* field has been added to the *Data Port Settings* menu. You can set the lightbar to output GGA messages with either six or seven decimal points.

Use this setting when you are outputting NMEA positions to a yield monitor that requires GGA positions at 6 decimal places.



- NMEA RMC messages no longer appear as blank messages when you use uncorrected GPS positions.
- The increment size for swath widths is now 1" or 0.01 m (1 cm).
- You can change the view from Plan to Perspective while defining a field.

- The *Antenna Offset* screen (which you access from the *Lightbar* menu) is now called the *Ant/Impl. Offset* screen.
- The roll value can be displayed as status text. To select this option, select the *Status Text* screen and then set one of the display options to Roll.
- The Roll value cannot be displayed when you use the lightbar with the AgGPS Autopilot automated steering system.
- When the system is configured to use US units, the *Ant/Axle Offset* and *Ant/Impl. Offset* screens display units in inches, instead of feet and inches.
- The Engage on AB option appears on different screens depending on which additional product is attached to the lightbar. If an AgGPS Autopilot system is connected to the lightbar, the Engage on AB option can be found on the *Guidance* screen. If an EZ-Steer assisted steering system is connected to the lightbar, the Engage on AB option can be found on *EZ-Steer / Engage Options*.
- EZ-Guide Plus system kits with the part number 52000-80-POR have a default lookahead of two seconds. To change this, select *Guidance / Look Ahead*.
- When you are driving a Headland pattern and you select the  icon to finalize the headland, the *Is this the final headland?* warning appears. Select Yes to confirm that it is the final Headland, or select No if you wish to create additional headlands.



---

**WARNING** – If the EZ-Guide Plus lightbar and an AgGPS 252 receiver are started at exactly the same time, the lightbar start-up sequence can stall and nothing is displayed on the lightbar screen. If this occurs, power up the receiver and the lightbar at different times.

---



---

**WARNING** – Correction types that you have not purchased may still be available for selection in the *Correction Types* field. Avoid selecting a correction type that you have not subscribed to, or you may receive low accuracy GPS positions.

---

## T2 Terrain Compensation Technology Operation

When the EZ-Guide Plus lightbar guidance system is connected to an EZ-Steer system controller with terrain compensation capability, the lightbar can make use of T2 terrain compensation technology for improved manual lightbar guidance.

**Note** – *To obtain assisted steering functionality, you require the complete EZ-Steer system, including the motor.*

### Setting up T2 technology

1. Securely bolt the EZ-Steer controller to the floor or to a low position on the rear wall of the cab.
2. Connect the controller to the system and then supply power.  
The *Terrain Comp.* menu will now be available.
3. Select *Terrain Compensation / Antenna Height* and set the antenna height.
4. Select *Terrain Compensation / Orientation* and set the controller orientation.
5. Select *Terrain Compensation / Calibration* and complete the terrain compensation calibration procedure.
6. Select *EZ-Steer / Axle/Ant Offset* and set the axle-to-antenna offset.
7. Select *EZ-Steer / EZ-Calibration* to run the EZ-Calibration wizard.

## T2 filter settings

If you have an EZ-Steer assisted steering system, use the following table as a guide to select the most appropriate filter option for your vehicle. These filter options have been optimized for different vehicle and field conditions. The manufacturer recommends you use the default Heavy3 filter option unless you experience poor performance.

Filter setting	Description
Roll only	May give good results when operating a sprayer with a suspended cab at speeds above 19.3 kph (12 mph).
Heavy3 (default)	This filter option provides good performance with all antenna locations and all speeds. This filter will almost always give the best accuracy if the antenna is on the roof of the vehicle or you are using curve, pivot, or headland patterns.

Select *Terrain Compensation / Filter* to change the filter.


## Recalibrate the EZ-Steer system for optimal performance with T2 technology (for existing users)

When you use the EZ-Steer system with T2 technology, you will usually need to increase the *Aggressiveness* setting and the *Freeplay™* technology left and right values compared to optimal EZ-Steer calibration settings without T2 technology.


## Optimizing EZ-Steer system calibration for curves

To obtain smoother steering when operating on curves, try setting the *Aggressiveness* lower than the optimal *Aggressiveness* setting for straight lines. To do this, select *EZ Steer / Vehicle Setup*.

This figure shows the system operating on a curve when the *Aggressiveness* is set correctly:



This figure shows the system operating on a curve when the *Aggressiveness* is too high:



---

## Upgrade procedure

To upgrade your EZ-Guide Plus lightbar to firmware version 4.00:

1. Download and install the EZ-Toolbox™ software version 2.10 from [www.EZ-Guide.com](http://www.EZ-Guide.com).
2. Download the firmware version 4.00 from [www.EZ-Guide.com](http://www.EZ-Guide.com).
3. Follow the instructions in the *EZ-Toolbox Software User Guide*. The *User Guide* is provided with the software.
4. If you also own the EZ-Steer system, use the EZ-Toolbox software to upgrade the EZ-Steer controller firmware to version 4.00. Go to [www.EZ-Steer.com](http://www.EZ-Steer.com).

**Note** – *Saved vehicle configurations from previous versions of the firmware are incompatible with the version 4.00 firmware. For more information, see Enhancements to saved vehicle configurations on page 6.*